CREATIVE DEPARTMENT
ARTWORK SPECIFICATIONS

Brand: PUR
Category: Faucet Mount PDS Sheet
Model: **PDS_FM_31ISFMNT191 WithOUT Turbidity**
Artwork Part #: 31ISFMNT192
Die Line Part #: N/A
Oracle Desc. : PRODUCT DATA SHEET FOR FAUCET MOUNT DEVICES WITHOUT TURBIDITY, REMOVE MTBE CLAIM
Subject: PDS Sheet
Region: US
Flat Size: IN: W11.000 x H15.750
MM: W279.400 x H400.050
Folded Size: IN: W5.5 x H5.25
MM: W139.700 x H133.350
Scale: 1/1
Material: Material: 50# White Matte Text
Page count: NA
Revision: 3
Date: **08JAN15**
Release Date: **09JAN14**
Rerelease Date:

Colors:
Dielines (Do not print)
Black
100%

Special Instructions:

Quality Requirement of Artwork and Quality Clarification Process of Artwork Printing: Meet Eng-QS-06&02

Kaz USA, Inc.
Creative Services, 250 Turnpike Road
Southborough, 01772 MA, USA
+1 508 490 7000

11.000"
279.400 mm
5.500"
139.700 mm
5.250"
133.350 mm
15.750"
400.050 mm
Copy Limit

ENGLISH

FILTER UNIT:

FM-2000B, FM-3333B	1 Filter Unit, 1 basic Filter Cartridge
FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B	1 Filter Unit, 1 mineralclear Filter Cartridge
FM-9000B, FM-9100B, FM-9400B, FM-9600B,	1 Filter Unit, 1 mineralclear Filter Cartridge

basic Faucet Mount Replacement Filter No, RF–3375
mineralclear Faucet Mount Replacement Filter No, RF–9999

FM-2000B, FM-3333B, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B
Systems Tested and Certified by NSF International against NSF/ANSI Standards 42 and 53 for the reduction of the claims specified on the Performance Data Sheet.

For system to perform as shown in the Performance Data Sheet, it is necessary to replace the filter when it exceeds filter capacity (100 gallons).
Testing was performed under standard laboratory conditions, actual performance may vary according to water conditions.
See owner's manual for operation and maintenance instructions.
The contaminants or other substances removed or reduced by this water filter are not necessarily in all users' water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts. Individuals requiring water of certain microbiological purity should consult their physician.
Replacement filters generally cost $19.99 each or less. Replacement filters may be purchased at most retail outlets or at purwater.com.

Technical Specifications

Filter Capacity	100 gallons (378 litres)/ up to 3 months
Rated Service Flow	0.52 gallons/minute (2.0 litres/minute) at 60 psig
Maximum Temperature	100°F (38°C)
Minimum Temperature	34°F (7°C)
Maximum Working Pressure	100 psig (690 kPa)
Minimum Working Pressure	20 psig (138 kPa)

Performance Data Sheet

For basic Faucet Unit Model No, FM-2000B, FM-3333B, Replacement Filter Model No, RF–3375. For advanced Faucet Unit Model No, FM–3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B.
Replacement Filter Model No, RF–9999,
These systems have been tested according to NSF/ANSI 42 and 53 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42 and 53.

Substance	PUR Reduction Data	NSF / ANSI Standard Requirements	
	Overall % Reduction	Influent challenge concentration (mg/L)	% Reduction Requirement / Maximum permissible product water concentration (mg/L)
Standard 42 - Aesthetic Effects			
Chlorine Taste and Odor	96%	2.0 mg/L ± 10%	≥ 50%
Nominal Particulate Class I particles 0.5 to <1 µm	98.8%	at least 10,000 particles/mL	≥ 85%
Standard 53 - Health Effects			
Asbestos	> 99%	>10^6 A.10^6 fibres/L fibres greater than 10 µm in length	99%
Cyst	> 99.99%	minimum 50,000/L	99.95%
2, 4-D	93.8%	0.210 ± 10%	0.07
2,4, 5-TP (Silvex)	99.7%	0.15 ± 10%	0.05
Atrazine	> 94.2%	0.009 ± 10%	0.003
Benzene	> 96.7%	0.015 ± 10%	0.005
Carbofuran	98.8%	0.08 ± 10%	0.04
Carbon Tetrachloride	96.8%	0.015 ± 10%	0.005
Chlordane	> 99.5%	0.04 ± 10%	0.002
Endrin	96.8%	0.006 ± 10%	0.002
Ethylbenzene	99.9%	2.1 ± 10%	0.7
Heptachlor Epoxide	99.6%	0.004 ± 10%	0.0002
Lead (pH6.5)	> 99.3%	0.15 ± 10%	0.010
Lead (pH8.5)	98.9%	0.15 ± 10%	0.010
Lindane	99%	0.002 ± 10%	0.0002
Mercury (pH6.5)	> 96.5%	0.006 ± 10%	0.002
Mercury (pH8.5)	96.0%	0.006 ± 10%	0.002
Methoxychlor	99.8%	0.12 ± 10%	0.04
Monochlorobenzene	>99.9%	2.0 ± 10%	0.1
o-Dichlorobenzene	> 99.9%	1.8 ± 10%	0.6
Simazine	98.5%	0.012 ± 10%	0.004
Styrene	> 99.9%	2.0 ± 10%	0.1
Tetrachloroethylene	> 96.7%	0.015 ± 10%	0.005
Toluene	> 99.9%	3.0 ± 10%	1
Toxaphene	92.9%	0.015 ± 10%	0.003
Trichloroethylene	> 99.8%	0.300 ± 10%	0.005
TTHM	99.7%	0.45 ± 20%	0.080
VOC (chloroform surrogate)	98.6%	0.300	0.015

VOC (reduction claims for organic chemicals included by chloroform surrogate testing)

Substance	Chemical Reduction %	Influent challenge concentration mg/L	Maximum permissible product water concentration mg/L
Alachlor	>98%	0.050	0.001
Atrazine	>97%	0.100	0.003
Benzene	>99%	0.081	0.001
Carbofuran	>99%	0.190	0.001
Carbon tetrachloride	98%	0.078	0.0018
Chlorobenzene	>99%	0.077	0.001
Chloropicrin	99%	0.015	0.0002
2,4-D	98%	0.110	0.0017
Dibromochloropropane (DBCP)	>99%	0.052	0.00002
o-Dichlorobenzene	>99%	0.087	0.001
p-Dichlorobenzene	>98%	0.040	0.001
1,2-Dichloroethane	95%	0.088	0.0048
1,1-Dichloroethylene	>99%	0.083	0.001
cis-1,2-Dichloroethylene	>99%	0.170	0.0005
trans-1,2-Dichloroethylene	>99%	0.086	0.001
1,2-Dichloropropane	>99%	0.080	0.001
cis-1,3-Dichloropropylene	>99%	0.079	0.001
Dinoseb	99%	0.170	0.0002
Endrin	99%	0.053	0.00059
Ethylbenzene	>99%	0.088	0.001
Ethylene dibromide (EDB)	>99%	0.044	0.00002
Haloacetonitriles (HAN): Bromochloroacetonitrile Dibromoacetonitrile Dichloroacetonitrile Trichloroacetonitrile	98% 98% 98% 98%	0.022 0.024 0.0096 0.015	0.0005 0.0006 0.0002 0.0003
Haloketones (HK): 1,1-dichloro-2-propanone 1,1,1-Trichloro-2-propanone	99% 96%	0.0072 0.0082	0.0001 0.0003
Heptachlor	>99%	0.025	0.00001
Heptachlor epoxide	98%	0.0107	0.0002
Hexachlorobutadiene	>88%	0.044	0.001
Hexachlorocyclopentadiene	>99%	0.060	0.000002
Lindane	>99%	0.055	0.00001
Methoxychlor	>99%	0.050	0.0001
Pentachlorophenol	>99%	0.096	0.001
Simazine	>97%	0.120	0.004
Styrene	>99%	0.150	0.0005
1,1,2,2-Tetrachloroethane	>99%	0.081	0.001
Tetrachloroethylene	>99%	0.081	0.001
Toluene	>99%	0.078	0.001
2,4,5-TP (silvex)	99%	0.270	0.0016
Tribromoacetic acid	>98%	0.042	0.001
1,2,4-trichlorobenzene	>99%	0.160	0.0005
1,1,1 -trichloroethane	95%	0.084	0.0046
1,1,2 - trichloroethane	>98%	0.150	0.0005
Trichloroethylene	>99%	0.180	0.0010
Trihalomethanes (includes): Chloroform (surrogate chemical) Bromoform Bromodichloromethane Chlorodibromomethane	95%	0.300	0.015
Xylenes (total)	>99%	0.070	0.001

ESPAÑOL

UNIDAD DE FILTRO:

FM-2000B, FM-3333B	1 unidad de filtro, 1 cartucho filtrante básico
FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B,	1 unidad de filtro, 1 cartucho filtrante mineralclear
FM-9000B, FM-9100B, FM-9400B, FM-9600B	1 unidad de filtro, 1 cartucho filtrante mineralclear

Filtro de repuesto para unidad de montaje para grifo básico núm, RF–3375
Filtro de repuesto para unidad de montaje para grifo mineralclear núm, RF–9999

FM-2000B, FM-3333B, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B
Sistemas evaluados y certificados por NSF International según las Normas 42 y 53 de NSF/ANSI relacionadas con las aseveraciones de reducción que se indican en la Hoja de especificaciones de rendimiento.

Para que el sistema rinda como se indica en la Hoja de especificaciones de rendimiento, es necesario reemplazar el filtro una vez excedida la capacidad del filtro (100 galones).
Las pruebas se realizaron bajo condiciones normales de laboratorio, el rendimiento real puede variar según las condiciones del agua.
Lea el Manual del propietario para obtener las instrucciones de mantenimiento y funcionamiento.
Los contaminantes u otras sustancias que este filtro de agua elimina o reduce no necesariamente se encuentran en el agua de todos los usuarios. No use con agua cuya seguridad microbiológica no haya sido constatada o cuya calidad sea desconocida sin una adecuada desinfección previa o posterior al uso del sistema de filtrado. Los sistemas certificados para la reducción de quistes se pueden usar en agua desinfectada que pudiera contener quistes filtrables. Las personas que requieran consumir agua de una pureza microbiológica específica deberán consultar a su médico.
Un filtro de repuesto normalmente cuesta $19.99 o menos. Los filtros de repuesto se pueden comprar en la mayoría de tiendas minoristas o en purwater.com.

Especificaciones técnicas

Capacidad del filtro:	100 galones (378 litros)/ hasta 3 meses
Flujo de servicio nominal:	0.52 galones/minuto (2.0 litros/minuto) a 60 psig
Temperatura máxima:	100 °F (38 °C)
Temperatura mínima:	34 °F (1 °C)
Presión de trabajo máxima:	100 psig (690 kPa)
Presión de trabajo mínima:	20 psig (138 kPa)

Hoja de especificaciones de rendimiento

Para una unidad de grifo básico modelos núm, FM-2000B, FM-3333B, Filtro de repuesto modelo núm. RF–3375. Para una unidad de grifo avanzado modelos núm, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-3800B, FM-4000B, FM-4100B, FM-9000B,FM-9100B, FM-9400B, FM-9500B, FM-9600B, FM-9700B. Filtro de repuesto modelo núm. RF–9999. Estos sistemas han sido evaluados según las Normas 42 y 53 de NSF/ANSI para la reducción de las sustancias enumeradas más abajo. La concentración de las sustancias indicadas en el agua que entran al sistema se redujo a una concentración menor o igual a la permitida en el agua al dejar el sistema, según las normas 42 y 53 de NSF/ANSI.

Sustancia	Datos de reducción PUR	Requerimientos de las normas de NSF/ANSI	
	% de reducción global	Concentración de influente (mg/l)	% de reducción requerido/Concentración máxima de agua procesada permitida (mg/l)
Norma 42 - Efectos estéticos			
Sabor y olor a cloro	96%	2.0 mg/L ± 10%	≥ 50%
Particulas nominales de Clase I particulas 0.5 a <1 µm	98.8%	por lo menos 10,000 particulas/ml	≥ 85%
Norma 53 - Efectos para la salud			
Asbesto	> 99%	>10^6 A.10^6 fibras/L fibras mayores que 10 µm en tamaño	99%
Quiste	> 99.99%	Mínimo 50,000/l	99.95%
2, 4-D	93.8%	0.210 ± 10%	0.07
2,4, 5-TP (Silvex)	99.7%	0.15 ± 10%	0.05
Atrazina	> 94.2%	0.009 ± 10%	0.003
Benceno	> 96.7%	0.015 ± 10%	0.005
Carbofurán	98.8%	0.08 ± 10%	0.04
Tetracloruro de carbono	96.8%	0.015 ± 10%	0.005
Clordano	> 99.5%	0.04 ± 10%	0.002
Endrina	96.8%	0.006 ± 10%	0.002
Etilbenceno	> 99.9%	2.1 ± 10%	0.7
Epóxido de heptacloro	99.6%	0.004 ± 10%	0.0002
Plomo (pH 6.5)	> 99.3%	0.15 ± 10%	0.010
Plomo (pH 8.5)	99.9%	0.15 ± 10%	0.010
Lindano	99%	0.002 ± 10%	0.0002
Mercurio (pH 6.5)	> 96.5%	0.006 ± 10%	0.002
Mercurio (pH 8.5)	96.0%	0.006 ± 10%	0.002
Metoxicloro	99.8%	0.12 ± 10%	0.04
Monoclorobenceno	>99.9%	2.0 ± 10%	0.1
o-Diclorobenceno	> 99.9%	1.8 ± 10%	0.6
Estireno	> 99.9%	2.0 ± 10%	0.1
Tetracloroetileno	96.7%	0.015 ± 10%	0.005
Tolueno	99.9%	3.0 ± 10%	1
Toxafeno	92.9%	0.015 ± 10%	0.003
Tricloroetileno	> 99.8%	0.300 ± 10%	0.005
Total de trihalometanos (TTHM)	99.7%	0.45 ± 20%	0.080
COV (cloroformo sustituto)	99.6%	0.300	0.015

VOC (aseveraciones de reducción para químicos orgánicos incluidos por las pruebas realizadas en el cloroformo sustituto)

Sustancia	% de reducción química	Concentración de influente (mg/l)	Concentración máxima de agua procesada permitida (mg/l)
Alacloro	>98%	0.050	0.001
Atrazina	>97%	0.100	0.003
Benceno	>99%	0.081	0.001
Carbofurán	>99%	0.190	0.001
Tetracloruro de carbono	98%	0.078	0.0018
Clorobenceno	>99%	0.077	0.001
Cloropicrina	99%	0.015	0.0002
2,4-D	98%	0.110	0.0017
Dibromocloropropano (DBCP)	>99%	0.052	0.00002
o-Diclorobenceno	>99%	0.087	0.001
p-Diclorobenceno	>98%	0.040	0.001
1,2-dicloroetano	95%	0.088	0.0048
1,1-dicloroetileno	>99%	0.083	0.001
cis-1,2-dicloroetileno	>99%	0.170	0.0005
trans-1,2-dicloroetileno	>99%	0.086	0.001
1,2-dicloropropano	>99%	0.080	0.001
cis-1,3-dicloropropileno	>99%	0.079	0.001
Dinoseb	99%	0.170	0.0002
Endrina	99%	0.053	0.00059
Etilbenceno	>99%	0.088	0.001
Dibromuro de etileno (EDB)	>99%	0.044	0.00002
Haloacetonitrilos (HAN): Bromocloroacetonitrilo Dibromoacetonitrilo Dicloroacetonitrilo Tricloroacetonitrilo	98% 98% 98% 98%	0.022 0.024 0.0096 0.015	0.0005 0.0006 0.0002 0.0003
Halocetonas (HK): 1,1-dicloro-2-propanona 1,1,1-tricloro-2-propanona	99% 96%	0.0072 0.0082	0.0001 0.0003
Heptacloro	>99%	0.025	0.00001
Epóxido de heptacloro	98%	0.0107	0.0002
Hexaclorobutadieno	>88%	0.044	0.001
Hexaclorociclopentadieno	>99%	0.060	0.000002
Lindano	>99%	0.055	0.00001
Metoxicloro	>99%	0.050	0.0001
Pentaclorofenol	>99%	0.096	0.001
Simazina	>97%	0.120	0.004
Estireno	>99%	0.150	0.0005
1,1,2,2-tetracloroetano	>99%	0.081	0.001
Tetracloroetileno	>99%	0.081	0.001
Tolueno	>99%	0.078	0.001
2,4,5-TP (silvex)	99%	0.270	0.0016
Ácido tribromoacético	>98%	0.042	0.001
1,2,4-triclorobenceno	>99%	0.160	0.0005
1,1,1-tricloroetano	95%	0.084	0.0046
1,1,2-tricloroetano	>99%	0.150	0.0005
Tricloroetileno	>99%	0.180	0.0010
Trihalometanos (incluye): Cloroformo (químico sustituto) Bromoformo Bromodiclorometano Clorodibromometano	95%	0.300	0.015
Xilenos (total)	>99%	0.070	0.001

FRONT

Purchases Made In Iowa / Compras hechas en Iowa

For purchases made in Iowa: / Para compras hechas en Iowa:
This form must be signed and dated by the buyer and seller prior to consummation of this sale. This form should be retained on file by the seller for a minimum of two years.
El vendedor y el comprador deben firmar y poner la fecha en este formulario antes de completar esta venta. El vendedor debe guardar este formulario por un periodo mínimo de dos años.

BUYER: / COMPRADOR:	SELLER: / VENDEDOR:
Name / Nombre	Name / Nombre
Address / Dirección	Address / Dirección
City / Ciudad	City / Ciudad
State / Estado — Zip / Código Postal	State / Estado — Zip / Código Postal
Signature / Firma — Date / Fecha	Signature / Firma — Date / Fecha

pur® Water Filtration System

Performance Data Sheet
Hoja de especificaciones de rendimiento

Model Numbers
FM-2000B, FM-3333B, FM-3333BNM, FM-3400B, FM-3500B, FM-3700B, FM-4000B, FM-4100B, FM-9000B, FM-9100B, FM-9400B, FM-9600B



Replace your filter every 100 gallons or up to three months of use

Reemplace su filtro cada 100 galones o hasta tres meses de uso.

Distr. by/por Kaz USA, Inc.
250 Turnpike Road, Southborough, MA 01772
1-800-PUR-LINE (1-800-787-5463) purwater.com
© 2015 All rights reserved. Kaz USA, Inc.

ENGLISH

Installation instructions



How to use



BEFORE FIRST USE, RUN COLD WATER FOR 5 MINUTES IN FILTERED WATER POSITION. DO NOT RUN HOT WATER THROUGH THE FILTER.
During filter flush, it is normal to see cloudy water and hear the sound of water pushing air out of the filter cartridge. Flushing removes any loose materials, which is normal.

If you need sink space or need to change the filter, remove the device from your faucet using the white Quick Release buttons.

For more information, see our how-to video at www.purwater.com/install

The light will turn on every time you use the filter.
Removal of filter cartridge resets the light.

For optimal use, care and safety

- Do not use with water above 100°F/38°C as this may damage the filter. Use with cold water only.
- After each new filter cartridge is installed, run the water for 5 minutes to flush it. Then, prior to each use, run water through the filter for 5 seconds to activate the filter.
- Clean the exterior of the faucet mount housing with a damp sponge or a soft cloth. A mild dishwashing liquid may also be used. Using anything else to clean your faucet mount could result in damage to the unit.
- Change your filter every 3 months for best performance.

Two Year Warranty

Kaz (Warranton), warrants your PUR Faucet Mount Water Filter Unit for two (2) years from the date of purchase (except for the filter cartridge which is warranted for 30 days) against all defects in materials and workmanship, when used in compliance with the owner's manual. If the product proves to be defective within two years from the date of purchase, call 1-800-787-5463. The warrantor assumes no responsibility for incidental or consequential damages; for damages arising out of misuse of the product or use of any unauthorized attachment; or for damages resulting from the use of the product with a defective water faucet. Some states do not allow the exclusion or limitation of incidental or consequential damages; so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other legal rights which vary from state to state. System complies with applicable state and local regulations. Should service be required or you have any questions regarding how to use your PUR product, please call PUR Consumer Relations at 1-800-787-5463, or US consumers visit our website at purwater.com.

ESPAÑOL

Instrucciones de instalación

Modo de empleo

ANTES DE USAR POR PRIMERA VEZ, HAGA CORRER AGUA FRÍA DURANTE 5 MINUTOS EN LA POSICIÓN DE AGUA FILTRADA. NO DEJE CORRER AGUA CALIENTE POR EL FILTRO.
Es normal que al lavar el filtro el agua se vea turbia y se oiga el sonido del agua expulsando el aire fuera del cartucho de filtración. Esta limpieza común y corriente ayuda a eliminar particulas sueltas.

Si necesita más espacio en su lavabo o necesita cambiar el filtro, quite el dispositivo del grifo al oprimir los botones blancos de liberación rápida (Quick Release).

Para obtener más información, vea nuestro video en www.purwater.com/install

La luz se enciende cada vez que usa el filtro.
La luz se vuelve a configurar al quitar el cartucho de filtración.

Para seguridad, cuidado y uso óptimos

- No use con agua que sobrepase los 100 °F/38 °C, ya que puede dañar el filtro. Use solo con agua fría.
- Después de instalar un nuevo cartucho de filtración, deje correr el agua durante 5 minutos para lavarlo. Luego, antes de cada uso, haga correr agua a través del filtro por 5 segundos para activar el filtro.
- Limpie el exterior de la cubierta de la unidad de montaje para grifo con una esponja húmeda o un paño suave. También puede usar un líquido para el lavado de platos suave. Si usa cualquier otro producto para limpiar la unidad de montaje para grifo, podría dañarla.
- Para obtener el mejor desempeño, cambie el filtro cada 3 meses.

Garantía de Dos Años

Kaz (Garante), garantiza su Unidad PUR de Filtración de Agua Montada al Grifo por dos (2) años a partir de la fecha de compra (excepto el cartucho del filtro que está garantizado por 30 días) contra todos los defectos en materiales y mano de obra, cuando se use de acuerdo con el manual del propietario. Si el producto resultara defectuoso en el plazo de dos años a partir de la fecha de compra, llame al 1-800-787-5463. El garante no asume responsabilidad alguna por daños indirectos o secundarios, daños que surjan del uso inapropiado del producto o del uso de accesorios no autorizados; o daños causados por el uso del producto con un grifo de agua defectuoso. Algunos estados no permiten la exclusión o la limitación de daños indirectos o secundarios; por lo tanto, es posible que la limitación o exclusión anterior no se aplique en su caso. Esta garantía le concede derechos legales específicos y es posible que tenga otros derechos legales que varían de un estado a otro. El sistema cumple con las normas locales y estatales correspondientes. En caso de necesitar servicio técnico o tener preguntas sobre el uso del producto PUR, llame al servicio al consumidor de PUR al 1-800-787-5463, o si reside en los EE. UU., visite nuestro sitio web purwater.com.

31ISFMNT192

BACK