

# Performance Data Sheet

**Model: Body Glove BG-12000** Use Replacement Cartridge BG-12000C

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42, Standard 53 and Standard 401.



System tested and certified by NSF International against NSF/ANSI Standard 42, Standard 53 and Standard 401 for the reduction of substances listed below.

Capacity 1000 Gallons (3785 Liters) Contaminant Reduction Determined by NSF testing.

Contaminant Reduction	Average Influent	NSF specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.1 mg/L	2.0 mg/L ± 10%	97.7%	0.07 mg/L	N/A	≥ 50%	J-00125570
Nominal Particulate Class I, ≥0.5 to < 1.0 µm	4,066,667 pts/mL	At least 10,000 particles/mL	99.9%	2565 pts/ml	N/A	≥85%	J-00125785
Chloramine	3.1 mg/L	3.0 mg/L ± 10%	97.7%	0.07 mg/L	0.5 mg/L	N/A	J-00125570
Asbestos	148 MFL	10 <sup>7</sup> to 10 <sup>8</sup> MFL; fibers greater than 10 µm in length	>99%	< 1MLF	N/A	≥99%	J-00125571
Cyst*	120,000 cysts/L	Minimum 50,000 cysts/L	99.98%	<1 cyst/L	N/A	≥99.95%	J-00125784
Lead pH @6.5	0.148 mg/L	0.15 mg/L ± 10%	>99.3%	0.001 mg/L	0.010 mg/L	N/A	J-00125572
Lead pH @8.5	0.150 mg/L	0.15 mg/L ± 10%	>99.3%	0.001 mg/L	0.010 mg/L	N/A	J-00125573
VOCs	0.308 mg/L	0.300 mg/L ± 10%	99.8%	0.0005 mg/L	N/A	≥95%	J-00125574
TTHMs	0.412 mg/L	0.45 mg/L ± 20%	99.9%	0.0005 mg/L	0.080 mg/L	N/A	J-00125579
MTBE	0.016 mg/L	0.015 mg/L ± 20%	>96.8%	0.0005 mg/L	0.005 mg/L	N/A	J-00125575
Bisphenol A	2100 ng/L	2000 ng/L ± 20%	>99.0%	20 ng/L	300 ng/L	N/A	J-00147834
Estrone	153 ng/L	140 ng/L ± 20%	>96.7%	5 ng/L	20 ng/L	N/A	J-00147834
Ibuprofen	440 ng/L	400 ng/L ± 20%	>95.5%	20 ng/L	60 ng/L	N/A	J-00147834
Naproxen	152 ng/L	140 ng/L ± 20%	>96.7%	5 ng/L	20 ng/L	N/A	J-00147834
Nonyl Phenol	1750 ng/L	1400 ng/L ± 20%	>97.1%	50 ng/L	200 ng/L	N/A	J-00163438
Phenytoin	217 ng/L	200 ng/L ± 20%	>95.4%	10 ng/L	30 ng/L	N/A	J-00147834

\* Based on the use of Cryptosporidium parvum oocysts

Contaminant reduction testing is conducted every five years by certifying agency to maintain certification.

The compounds certified under NSF 401 have been deemed as “emerging compounds/incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

# Performance Data Sheet

Model: Body Glove BG-12000 Use Replacement Cartridge BG-12000C

Application Guidelines/Water Supply Parameters	
Service Flow	0.75 gpm (2.8 lpm)
Water Supply	Potable Water
Water Pressure	25 - 125 psi (172 – 862 kPa)
Water Temperature	40° F - 100° F (4.4° C - 38° C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary. Contaminant reduction testing is conducted every five years by certifying agency to maintain certification.

Replacement Cartridge: BG-12000C. For estimated costs of replacement elements please call 1-800-322-9283 or visit our website at [www.waterinc.com](http://www.waterinc.com)



## WARNING

**Read entire manual. Failure to follow all guides and rules could cause personal injury or property damage.**

- Check with your local public works department for plumbing codes. You must follow their guidelines as you install the Water Filtration system.
- Your Water Filtration system will withstand up to 125 pounds per square inch (psi) water pressure. If your house water supply pressure is higher than 80 psi, install a pressure reducing valve before installing the Water Filtration system.

### To reduce the risk associated with the ingestion of contaminants:

DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

EPA Establishment Number 10350-MN-007

### NOTICE:

#### To reduce the risk associated with water leakage or flooding:

- Read and follow Use Instructions before installation and use of this system.
- Change the disposable filter cartridge at the recommended interval; the disposable filter cartridge MUST be replaced every 6 months or sooner.
- Failure to replace the disposable filter cartridge at recommended intervals may lead to reduced filter performance and failure of the filter, causing property damage from water leakage or flooding.

Parts and service available from:



Water, inc.  
1044 East Del Amo Blvd  
Carson, CA 90746  
Toll Free: 1-800-322-9283  
Fax: 310 885-4385  
[www.waterinc.com](http://www.waterinc.com)