

2012 ANNUAL WATER QUALITY REPORT

Santa Ynez River Water Conservation District,

Improvement District No. 1

BOARD OF TRUSTEES:

Division 1 - Los Olivos Division 2 - Solvang Division 3 - Solvang Division 4 - Santa Ynez At-Large Harlan Burchardi Dennis Beebe Lawrence F. Musgrove Harry Poor Karen Carroll

Office Location: 3622 Sagunto Street Santa Ynez, CA 93460 Mailing Address: P.O. Box 157 Santa Ynez, CA 93460

Phone # (805) 688-6015

Fax # (805) 688-3078

2012 ANNUAL WATER QUALITY REPORT

Santa Ynez River Water Conservation District, Improvement District No. 1 (District)

To All District Customers:

This report provides a summary of the water quality results from sampling of District water supply wells, distribution system, and State Water supplies for the 2012 calendar year. As a public water purveyor to the communities of Santa Ynez, Los Olivos, Ballard, the City of Solvang, and the Santa Ynez Band of Chumash Indians, the District operates under a permit issued by California Department of Public Health (DPH). In accordance with this Water Supply Permit and California Safe Drinking Water regulations, the District routinely tests all ground water sources for a complete set of potential contaminants as well as other water quality constituents. State Water supplies are similarly tested by the Central Coast Water Authority (CCWA). The results of these sampling and monitoring efforts for the 2012 calendar year are included in this report, along with additional information regarding your water supplies. Analytical data presented in this report represent the quality of the water delivered daily to you through your water service connection.

District water sources in use in 2012:

1) Ground Water – 15 supply wells

In 2012, the District operated seven of eight (8) active supply wells pumping ground water from the Santa Ynez Upland ground water basin. Bounded by the foothills of the San Rafael Mountains to the north, this wedge-shaped area encompasses approximately 130 square-miles, paralleling the Santa Ynez River to the south and narrowing east to Red Rock Canyon. Active District wells in the Upland Basin range in depth from less than 500 feet to over 1,300 feet. The production rate (i.e., flow rate) of these "Upland" wells ranges from 350 to over 1,300 gpm (gallons/minute).

Separated from the southern margin of the Upland Basin by a barrier of impermeable rocks are the water-bearing alluvial (sand and gravel) deposits that fill the trough-like channel carved within the Santa Ynez River floodplain. During 2012, the District utilized seven (7) wells constructed in these alluvial deposits to a maximum depth of approximately 70 feet. The production rate of these wells ranges from 150 to 650 gpm.

2) Surface Water – State Water Project

While the District still maintains an annual entitlement to water from Cachuma Lake, the only source of surface water served by the District comes from the State Water Project. The District's entitlement from the Cachuma Project is exchanged for an equal amount of State Water under an "Exchange" agreement with water agencies on the south coast of Santa Barbara County. In addition to the exchanged Cachuma water, the District also receives State Water directly by entitlement. Surface water from the California Aqueduct is treated at the Polonio Pass Water Treatment plant in Kern County prior to entering the 143-mile long pipeline en route to the District's Mesa Verde Pumping Plant in Santa Ynez. State Water supplies made up approximately 54 percent of the District's total supply in 2012.

The District maintained eight (8) inactive wells during the 2012 calendar year: four wells located in the Upland Basin; and four wells located adjacent to the active Santa Ynez River channel. Wells are designated inactive for a variety of reasons including operational restrictions, regulatory requirements, and water quality parameters.

Drinking Water Source Assessments

The 1996 Amendments to the Federal Safe Drinking Water Act established the Drinking Water Source Assessment and Protection (DWSAP) Program to assess all sources of drinking water for vulnerability to contamination and to establish source protection programs. The District has evaluated each of the well locations in the District following the program guidelines. In summary, potential contaminant sources in the Upland Basin include septic systems and agricultural drainage. Contaminant sources that have the potential to affect wells located within the Santa Ynez River floodplain include septic systems, other wells (active and abandoned), agricultural drainage, upstream contaminant sources, application of agricultural chemicals, and surface runoff from roads. All completed assessments are available for viewing at the District office.

For the 2012 reporting period, the only contaminant associated with these PCAs detected in any of the wells was nitrate. Nitrate was detected in all of the operating Upland Basin wells, with concentrations ranging from 5.5 to 15 parts per million (ppm). Nitrate was not detected in any of the active river wells. Annual monitoring of all water supply wells is required to assure that concentrations remain below the 45 ppm Maximum Contaminant Level (MCL) for nitrate. Should nitrate concentrations exceed one-half the MCL, more frequent (quarterly) monitoring would be required.

TERMS USED IN THIS REPORT:

Maximum Contaminant Level (MCL): The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to make drinking water aesthetically pleasing (i.e., protect the odor, taste, and appearance of the water).

Primary Drinking Water Standards (PDWS): MCLs for contaminants that affect health along with their monitoring, reporting, and water treatment requirements.

Secondary Drinking Water Standards (SDWS): MCLs for contaminants that affect taste, odor, or appearance of the drinking water. Contaminants with SDWSs do not affect health at the established MCL.

Maximum Residual Disinfectant Level Goal (MRDLG): The level of a disinfectant added for water treatment below which there is no known or expected risk to health. MRDLGs are set by the U.S. Environmental Protection Agency. **Maximum Residual Disinfectant Level (MRDL)**: The level of a disinfectant added for water treatment that may not be exceeded at the consumer's tap.

Public Health Goal (PHG): The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the Office of Environmental Health and Hazard Assessment (OEHHA).

Maximum Contaminant Level Goal (MCLG): The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency (USEPA).

Regulatory Action Level (AL): The concentration of a contaminant which, if exceeded, triggers treatment or other requirements which a water system must follow.

Detection Limit for the Purposes of Reporting (DLRs): The minimum concentration a certified laboratory must detect for a given analytical parameter to comply with State regulations.

Treatment Technique (TT): A required process intended to reduce the level of a contaminant in drinking water.

Potential Contaminants in Source Water

Federal regulation requires the following information to be included in this report. Because it is general information, it does not necessarily apply to the drinking water provided by the District. Information specific to your drinking water is found in the summary table below.

In general, sources of both tap water and bottled water include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity. Contaminants that could be present in source water include the following:

- *Microbial contaminants*, such as viruses and bacteria that may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife.
- *Inorganic contaminants*, such as salts and metals that can be naturally-occurring or result from urban stormwater runoff, industrial or domestic wastewater discharges, oil and gas production, mining, or farming.
- *Pesticides and herbicides*, which may come from a variety of sources such as agriculture, urban stormwater runoff, and residential uses.
- *Organic chemical contaminants*, including synthetic and volatile organic chemicals that are byproducts of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff, and septic systems.
- *Radioactive contaminants*, which can be naturally-occurring or be the result of oil and gas production and mining activities.

In order to ensure that tap water is safe to drink, the U.S. Environmental Protection Agency (USEPA) and the State Department of Public Health (DPH) prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. DPH regulations also establish limits for contaminants in bottled water that require the same level of protection for public health.

EPA Safe Drinking Water Hotline

All drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that the water poses a health risk. Regulations in California establish limits requiring bottled water to provide the same protection of public health as the public water purveyor. More information about contaminants and potential health effects is available on-line at the U.S. Environmental Protection Agency's (EPA) Safewater website at *http://www.epa.gov/safewater* on the Internet or by calling the EPA Safe Drinking Water Hotline (1-800-426-4791).

Additional Information Regarding Your Drinking Water

<u>Nitrate</u>

Nitrate in drinking water at levels above 45 mg/L is a health risk for infants of less than six months of age. Such nitrate levels in drinking water can interfere with the capacity of the infant's blood to carry oxygen, resulting in a serious illness; symptoms include shortness of breath and blueness of the skin. Nitrate levels above 45 mg/L may also affect the ability of the blood to carry oxygen in other individuals, such as pregnant women and those with certain specific enzyme deficiencies.

Hexavalent Chromium (Cr+6)

Chromium is a naturally occurring metal present in ore deposits and rock types found in the nearby San Rafael Mountains, which make up a large portion of the Upland Basin watershed area that recharges the District's ground water wells. As a result, chromium (including Cr+6) is present in the District's active Upland Basin water supply wells in concentrations ranging from Non-Detect to 32 ppm. These concentrations are in compliance with the current Federal and State regulatory standards (i.e. MCLs) of 100 ppm and 50 ppm, respectively. The pending establishment of a new Cr+6 MCL by the State of California could affect the District's groundwater supply and cause financial and operational impacts. The District is anticipating the announcement by DPH of a draft MCL for Cr+6 in July 2013and will remain proactive in complying with evolving water quality regulations and ensuring a safe and reliable water supply.

Recommendation for Customers with Special Water Needs

Some people may be more vulnerable to contaminants in drinking water than the general population. Immunocompromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. USEPA/Centers for Disease Control (CDC) guidelines on appropriate means to lessen the risk of infection by *Cryptosporidium* and other microbial contaminants are available from the Safe Drinking Water Hotline (1-800-426-4791).

Analytical Results

The following summary table of analytical results lists the range and average concentrations of the drinking water contaminants (as well as other water quality constituents) that were detected during the most recently required sampling for each source and constituent listed. Also listed are results of the District's required distribution system sampling. It is worth noting that chemicals not detected are not included in the report. Additionally, DPH sampling requirements allow for source monitoring of certain contaminants less than once per year because the concentrations of these contaminants do not vary significantly from year to year. Therefore, some of the data listed in the tables, though representative of the source water quality, are more than a year old.

SAMPLING RESULTS: PRIMARY AND SECONDARY STANDARDS

			Drinking \	Drinking Water Source						
		State	PHG	State	Range	State		Ground		
Parameter	Units	MCL	(MCLG)	DLR	Average	Water		Water	Major Sources in Drinking Water	
PRIMARY STANDARDSMandatory Health-Related Standards										

CLARITY^a

Combined Filter	NTU	TT=<1 NTU every 4 hours	Range	0.04 - 0.13	NA	Soil runoff
Effluent Turbidity	NIO	TT=95% of samples <0.3 NTU	%	100%	NA	

INORGANIC CHEMICALS

	-							
Aluminum ^b	ppb	1000	600	50	Range	ND - 120	ND	Residue from water treatment process;
Aluminum	ppp	1000	000	50	Average	69	ND	Erosion of natural deposits
Arsenic	ddd	10	0.004	2.0	Range	ND	ND - 2.4	Erosion of natural deposits; runoff from orchards
/	PPD	10	0.004	2.0	Average	ND	0.5	glass and electronic production waste
Barium	ppb	1000	2000	100	Range	ND	ND - 170	Erosion of natural deposits; oil drilling
Danum	ppp	1000	2000	100	Average ND		29.0	and metal refinery wastes
Chromium (Total Cr)	ppb	50	(100)	10	Range	ND	ND - 27	Erosion of natural deposits; steel,
Chronnunn (Total Cr)	ppp	50	(100)	10	Average	ND	8.9	pulp mills, and chrome plating wastes
Fluoride	nnm	2	1	0.1	Range	ND	ND - 0.34	Erosion of natural deposits;
Fidolide	ppm	2			Average	ND	0.25	water additive for tooth health
Nickel	nnh	100	12	10	Range	ND	ND - 12	Erosion of natural deposits; runoff from orchards
NICKEI	ppb	100	12	10	Average	ND	1.2	glass and electronic production waste
					Range	0.49	ND - 4.1	Runoff and leaching from fertilizer use; leaching
Nitrate + Nitrite (as N)	ppm	10	10	0.4	Average	0.49	1.9	from septic tanks and sewage; erosion of natural deposits
					Range	2.2	ND - 15	Runoff and leaching from fertilizer use; leaching
Nitrate (as NO ₃)	ppm	45	45	2	Average	2.2	5.1	from septic tanks and sewage; erosion of natural deposits

RADIONUCLIDES

C C	0.1	15			Range	ND	ND - 7.3	Erosion of natural deposits	
Gross Alpha	pCi/L	15	NA	3	Average	ND	3.1		
Uranium	pCi/L	20	0.5	4	Range	NC	2.8	Erosion of natural deposits	
Oranium	poi/L	20	0.5	I	Average	NC	2.8		

SECONDARY STANDARDS--Aesthetic Standards

		500	NIA		Range	46 - 146	35 - 66	Runoff/leaching from natural deposits;
Chloride	ppm	500	NA		Average	86	46	seawater influence
	11.20	45	NIA		Range	ND	ND - 9	Next will be a state of the second state
Color (ACU)	Units	15	NA		Average	ND	1.0	Naturally-occurring organic materials
Corrosivity	SI	non-	NA		Range	non-	non-	Balance of hydrogen, carbon, & oxygen in
Contosivity	0	corrosive			Average	corrosive	corrosiv	e water, affected by temperature & other factors
Iron	nnh	300	NA	100	Range	ND	ND - 27	D Leaching from natural deposits;
lion	ppb	300	NA NA	100	Average	ND	100	industrial wastes
Foaming Agents	nnh	500	NA		Range	NA	ND - 12	Municipal and industrial waste discharge
(MBAS)	ppb	500	INA		Average	NA	12	
Odor Threshold	Units	3	NA	1	Range	ND	ND - 1	
	Units	5	NA NA		Average	ND	0.6	Naturally-occurring organic materials
Specific	µmho/	1600	NA		Range	344 - 706	760 - 110	0 Substances that form ions
Conductance	cm	1000	NA NA		Average	522	880	when in water; seawater influence
Sulfate	n nm	500	NA	0.5	Range	71	13 - 240	Runoff/leaching from natural deposits;
Suilale	ppm	500	NA	0.5	Average	71	120	industrial wastes
Total Dissolved	nnm	1000	NA		Range	202 - 417	440 - 76	Runoff/leaching from natural deposits;
Solids	ppm	1000	NA		Average	308	554	nunon/leaching nom natural deposits,
Lab Turbidity (ID#1)	NTU	5	NA		Range	0.04 - 0.1	ND - 1.0	3 Soil runoff
Turbidity (State Water)	NIU	5	NA		Average	0.05	0.35	

ADDITIONAL PARAMETERS (Unregulated)

Alkalinity (Total) as	nnm	NA	NA	Range	46 - 86		260 - 330	Runoff/leaching from natural deposits;
CaCO ₃ equivalents	ppm NA		NA NA	 Average	67		291	seawater influence
Calcium	ppm	NA	NA	 Range	30 - 76		43 - 110	Runoff/leaching from natural deposits;
Calcium		INA.		 Average	49		78	seawater influence
Hardness (Total) as	nnm	NA	NA	 Range	64 - 156		280 - 490	Leaching from natural deposits
CaCO ₃	ppm	NA .	INA.	Average	101		382	Leaching north natural deposits

						Drinking Wa	ate	er Source	
Parameter	Units	State MCL	PHG (MCLG)	State DLR	Range Average	State Water		Ground Water	Major Sources in Drinking Water
Heterotrophic Plate	CFU/mL	тт	NA		Range	0 - 4		NC	Naturally present in the environment
Count ^d			NA		Average	0.6		NC	Naturally present in the environment
Magnesium	ppm	NA	NA		Range	13		49 - 84	Runoff/leaching from natural deposits;
Magnesium	ppin	NA .			Average	13		59	seawater influence
Ηα	рН	NA	NA		Range	7.2 - 8.8		7.1 - 8.1	Runoff/leaching from natural deposits;
рп	Units	NA	NA		Average	8.3		7.6	seawater influence
Potassium	nnm	NA	NA		Range	2.6		1.6 - 2.4	Runoff/leaching from natural deposits;
Folassium	ppm	INA	NA.		Average	2.6		2.1	seawater influence
Sodium	nnm	NA	NA		Range	62	I	34 - 52	Runoff/leaching from natural deposits;
Sodiam	ppm	NA	NA		Average	62		41	seawater influence
Total Organic Carbon	nnm	тт	NA	0.30	Range	1.4 - 2.4			Various natural and manmade sources.
(TOC) ^e	ppm	11	NA	0.30	Average	1.8			vanous naturai and maninade sources.

Constituents of Con	Constituents of Concern											
Boron	ppb	NA	NL=1,000	100	Range	NC	ND - 310					
Beron	ppp		NL=1,000	100	Average	NC	153					
Chromium (. C)	nnh	NIA	0.00	4	Range	NC	ND - 32					
Chromium (+6)	ppb	NA	0.02	Ι	Average	NC	8.8					
Vanadium	dqq	NA	NL=50	S	Range	NC	ND - 18					
Vanadidin	ppp	11/5	NL=00	5	Average	NC	11.2					

Distribution System Water Quality

MICROBIOLOGICAL

Total Coliform (TC)	5.0% of		Range	0 Positives				
Bacteria ^f	 monthly	0	 Average	0 Positives			Naturally present in the environment	
CCWA Distribution	samples		Highest	0 Positives				
Total Coliform Bacteria	>1 positive	0	Highest #		0 Do	aitiya	Naturally present in the anyironment	
ID#1 Distribution	per month	0	 pos / mo		2 Positive		Naturally present in the environment	
Fecal Coliform			Range	0 Positives				
and <i>E. Coli</i>	 	0	 Average	0 Positives			Human and animal fecal waste	
CCWA Distribution			Highest	0 Positives				
Fecal Coliform	1 positive;		Highest #		1 Po	sitive		
and <i>E. Coli</i>	 with repeat	0	 pos / mo		0 Po	sitive,	Human and animal fecal waste	
ID#1 Distribution	TC positive		w/ repeat		w/	TC +		

ORGANIC CHEMICALS

T	daa	80	NA	NA	Range	20 - 77	7.9 - 59.5	By-product of drinking water
Total Trihalomethanes ⁹	ppp	00			Highest	46	40.9	chlorination
9	daa	60	NA	1 o ^h	Range	5.4 - 17	1.6 - 21.5	By-product of drinking water
Haloacetic Acids ⁹	php	00	INA	1,2	Highest	11	13.7	chlorination

DISINFECTION

Total chlorine residual		MRDL =	MRDLG =	Range	1.5 - 3.1			Measurement of the disinfectant	
CCWA Distribution	ppm	4.0	4.0	 Average	2.2			used in the production of drinking water	
Free/total chlorine residual		MRDL =	MRDLG =	Range		(0.1 - 2.5	Measurement of the disinfectant	
ID#1 Distribution	ppm	4.0	4.0	 Average			1.4	used in the production of drinking water	

Abbrevations and Notes

Footnotes:

- (a) Turbidity (NTU) is a measure of the cloudiness of the water and is a good indicator of the effectiveness of a filtration system. Monthly turbidity values for State Water are listed in the Secondary Standards section.
- (b) Aluminum has a Secondary MCL of 200 ppb.
- (c) Gross alpha particle activity monitoring required every nine years for State Water. Reported average represents highest running source average.
- (d) Pour plate technique -- monthly averages.
- (e) TOCs are taken at the State Water treatment plant's combined filter effluent.
- (f) Total coliform MCLs: No more than 5.0% (State Water) or 1 sample (ID#1) of the monthly samples may be Total Coliform positive. All required follow-up and confirmation samples collected in response to each of the positive Total Coliform samples were absent for Total Coliform.
- (g) Compliance based on the running quarterly annual average of distribution system samples. Values reported are range of all sample results and highest running annual average.
- (h) Monochloroacetic Acid (MCAA) has a DLR of 2.0 ug/L while the other four Haloacetic Acids have DLR's of 1.0 ug/L.

Abbreviations

ACU = Apparent Color Units

CCWA = Central Coast Water Authority

CFU/ml = Colony Forming Units per milliliter

- ID#1 = Santa Ynez River Water Conservation District, Improvement District No.1
- NA = Not Applicable
- NC = Not Collected
- NL = Notification Level
- NTU = Nephelometric Turbidity Units
- pCi/L = PicoCuries per liter
- ppb = parts per billion, or micrograms per liter (μ g/L)
- ppm = parts per million, or milligrams per liter (mg/L)
- TOC = Total Organic Carbon

µmho/cm = micromhos per centimeter

(unit of specific conductance of water)

	SAMP	LING RES	ULTS: DIS	TRIB	UTION S	YSTEM MONITOR	RING		
Microbiological Contaminants	No. of Samples Required*	No. of Samples Collected	Highest Number of detections		of months MCL		MCLG	Typical Source of Bacteria	
Total Coliform Bacteria	165	219	$($ In a mo. $)$ 2^1	1 ²		More than 1 sample in a month with a detection	0	Naturally present in the environment	
Fecal Coliform or <i>E. coli</i>	165	219	(In the year) 1^1		0	A routine sample and a repeat sample detect total coliform and either sample also detects fecal coliform or <i>E. coli</i>	0	Human and animal fecal waste	
Lead and Copper ³	No. of samples collected	90 th percentile level detected	No. Sites exceeding AL	AL	MCLG	Typical Source of Contaminant			
Lead (ppb)	20	ND	1	15 2		Internal corrosion of household water plumbing systems; discharges from industrial manufacturers; erosion of natural deposits.			
Copper (ppm)	20	.086 mg/L	0	1.3 0.17		Internal corrosion of household water plumbing systems; erosion of natural deposits; leaching from wood preservatives.			

Notes:

1. All repeat and confirmation samples were negative for coliform bacteria at each of the positive sample locations and all upstream and downstream sampling sites.

2. See MCL Violation below.

3. Sampling requirements are specified in the Lead and Copper Rule, California Code of Regulations (CCR), Title 22, Domestic Water Quality and Monitoring and are based on the population served. Samples are obtained from a representative sampling of customer's internal plumbing. Following initial sampling specified in CCR, Title 22, Chapter 17.5, representative sampling for lead and copper is required once every three years. The data summary displayed in the above table is from data obtained in August of 2012. The next sampling for lead and copper will be in the summer of 2015.

MCL Violation

Coliforms are bacteria that are naturally present in the environment and are used as an indicator that other, potentially harmful bacteria may be present. Two samples taken in April 2012, at different times and from separate water quality monitoring stations, indicated the presence of total coliform bacteria. This resulted in the violation of a drinking water standard and served as a warning of potential problems. All District customers received notice of this violation in July 2012, either by direct mail, public posting, or website notice. Based on the non-detect results of required repeat and nearby sampling, it was concluded that the positive coliform samples were caused by contamination of the sample station itself or a remnant of the sampling process (acquisition, handling, transport, etc.) and not a distribution system water quality issue. The District subsequently replaced the sample tap at each of the sample stations. No coliform bacteria have been detected during routine weekly sampling at either of these locations since replacement of the sample taps.

Cross-Connection Control Program

As many of our residential and commercial customers know, the District requires the installation and maintenance of backflow prevention devices where "an actual or potential cross-connection" exists, to protect and ensure safe water quality within our distribution system. Resolution No. 482 establishes the District's Cross-Connection Control Program to assure compliance with California Department of Health Services regulatory requirements (17 CCR, Section 7584) and to prevent the contamination of our distribution system. For additional

information regarding this program, pick up a copy of our free color cross-connection control brochure or the District's Cross-Connection Control policy at the District office, located in Santa Ynez at 3622 Sagunto Street.

Surface Water Supply – The State Water Project

As stated above, the surface water from State Water Project made up approximately 54 percent of the District's water supply for 2012. Runoff from the Sierra Nevada watershed travels more than 500 miles through the rivers, pipelines, and aqueducts that make up the State Water Project before reaching the District's Mesa Verde Pumping Station. This "State" water is treated at the Polonio Pass Water Treatment Plant (PPWTP), a 43 million-gallon per day facility designed and constructed to treat and purify all water served to San Luis Obispo and Santa Barbara Counties. The operation of the plant is the responsibility of the Central Coast Water Authority (CCWA), an agency formed in 1991 to finance, construct, and operate State water treatment and delivery facilities on behalf of all Santa Barbara County participants in the State Water Project. CCWA conducts weekly testing of the treated State water at numerous locations along its 143-mile pipeline route to Santa Ynez to assure the delivery of the highest quality treated water to their (and our) customers. For more information about the treatment and delivery of State water, please visit CCWA at the following web site: <u>www.ccwa.com</u>.

As a reminder, water from the State Water Project that is served throughout the District is disinfected with chloramines as the final step in the raw water treatment process. Chloramine treatment is an effective disinfectant and has resulted in reduced taste and odor complaints. While chloramines do not pose a health hazard to the general population, they can be dangerous to people undergoing kidney dialysis unless the chloramines are reduced to acceptable levels. Dialysis patients should already be aware of this concern and be taking the proper precautions when receiving dialysis treatment. Additionally, **chloraminated water is toxic to fish**. Local pet and fish suppliers should be contacted to obtain the necessary treatment for chloraminated water to assure it is safe for fish.

2013 Annual Water Quality Report (AWQR) – Electronic Delivery

In constant pursuit of ways to operate more efficiently and economically, next year the District will "electronically" deliver the 2013 AWQR to its customers. The electronic delivery method will allow the District to minimize printing and mailing costs, as well as reducing paper consumption. Next year's AWQR will not be mailed to every customer, as has been the customary practice, but will be available after June 30th at the District web site in the Water Quality Report section. Hard copies will be available at the District office and will be mailed upon request. Reminder notices and URL location will be posted on the monthly billing cards prior to July of next year.

Attention Landlords and Other Property Managers

We recommend that landlords and other property managers display this report in a public location such as a lobby, laundry room, or community room. If you would like to receive additional copies of this report, please contact the District office at (805) 688-6015.

Public Participation

If you are interested in learning more about your water supply, District customers and other members of the public are invited to attend the regularly scheduled meetings of the Board of Trustees on the **third Tuesday of** each month, 5:30 P.M., at the District Office, 3622 Sagunto Street, Santa Ynez.

District staff appreciate this opportunity to communicate our efforts in delivering a reliable, high quality drinking water to District customers. We are interested in any questions, suggestions or concerns you may have pertaining to this report or any other water quality issues. For additional information, please contact Eric Tambini, Assistant General Manager, at the District office [(805) 688-6015].

<u>Our Mission Statement</u>: To provide the residential and agricultural customers in the Santa Ynez River Water Conservation District, Improvement District No.1 service area with a reasonably priced, reliable, high quality water supply, and efficient and economical public services.

Atención, consumidores que hablan espanol: Este informe contiene información muy importante sobre su agua potable. Tradúzcalo o hable con alguien que lo entienda bien.

Source Water Protection Tips for our Customers

Each individual living within the watersheds of the Santa Ynez River and the Upland Groundwater Basin shares in the responsibility for the protection of local drinking water supplies. Ways for you to help protect your community's drinking water sources include the following:

- Eliminate excess use of lawn and garden fertilizers and pesticides they contain hazardous chemicals that can reach your drinking water source.
- Pick up after your pets.
- If you have your own septic system, properly maintain your system to reduce leaching into the shallow aquifer.
- Dispose of used and waste chemicals properly. For example, take used motor oil to a recycling center.

Water Conservation Tips for our Customers

Statistics show that the average U.S. household uses approximately 400 gallons of water per day. Fortunately, there are many low-cost ways to conserve water. Small changes in water usage can make a significant difference in your water consumption (and water bill) over time. Some water conservation measures you can use include, but are not limited to, the following:

- Take short showers a 5 minutes shower uses 4 to 5 gallons of water compared to up to 50 gallons for a bath.
- Shut off water while brushing your teeth, washing your hair and shaving and save up to 500 gallons a month.
- Use a water-efficient showerhead. They are inexpensive, easy to install, and can save you up to 750 gallons a month.
- Run your clothes washer and dishwasher only when they are full. You can save up to 1,000 gallons a month.
- Water plants only when necessary.
- Fix leaking toilets and faucets. Faucet washers are inexpensive and take only a few minutes to replace. To check your toilet for a leak, place a few drops of food coloring in the tank and wait. If it seeps into the toilet bowl without flushing, you have a leak. Fixing it or replacing it with a new, more efficient model can save up to 1,000 gallons a month.
- Adjust sprinklers so only your lawn is watered. Apply water only as fast as the soil can absorb it and during the cooler parts of the day to reduce evaporation.
- Teach your kids about water conservation to ensure a future generation that uses water wisely. Make it a family effort to reduce next month's water bill!
- Visit <u>www.sbwater.org</u> and <u>www.epa.gov/watersense</u> for more information.