Compton/Willowbrook 2013/2014

Consumer Confidence Report and Annual Water Quality Report



Park Water Company (Park) is pleased to provide you with a copy of this year's Annual Water Quality Report. We have put together a series of articles that we hope will keep you better informed on water quality issues both in general and specific to what comes from your own tap. Please feel free to contact us should you ever have any questions about service or quality.

Este informe contiene informacion muy importante sobre su agua potable. Traduzcalo o hable con alguien que lo entienda bien.

Where Your Water Comes From

In 2013, the Park Compton/Willowbrook system obtained 86% of its source water from the Metropolitan Water District of Southern California (MWD). The MWD imports water from the Colorado River Aqueduct and from the Sacramento-San Joaquin Delta by way of the State Water Project. An additional 14% came from deep wells that pump ground water from the Central Basin aquifer.

About the Metropolitan Water District of Southern California

MWD is a consortium of 26 cities and water districts that provides drinking water to nearly 19 million people in parts of Los Angeles, Orange, San Diego, Riverside, San Bernardino and Ventura counties. MWD currently delivers an average of 1.7 billion gallons of water per day to a 5,200-square-mile service area. The mission of the MWD is to provide its service area with adequate and reliable supplies of high-quality water to meet present and future needs in an environmentally and economically responsible way. MWD continues to add storage and conservation resources to its already diverse water supply portfolio to insure a reliable water supply well into the future. Further, MWD continues to invest in water quality improvements, including the addition of ozone as a treatment process and the expansion of its treatment capacity that will provide excellent water quality. For more information about MWD, visit their website at www.mwdh2o.com.

Two Sources of Imported Water Makes a Difference in the Hardness of Your Water

With the decreased availability of State Water Project water to blend with Colorado River water, water supplied to the Park Compton/Willowbrook system by MWD has increased in hardness as Colorado River water now dominates as the source. The Park Comtpon/Willowbrook system now receives the majority of its water from the MWD Diemer filtration plant in Yorba Linda. In 2013, the Diemer plant source water consisted of 23% State Project water (range from 0 to 58%) and 77% Colorado River water, as opposed to 100% State Project water in recent years. This is why the water quality shown in the center of this report shows increases from previous years in sulfate, alkalinity, calcium and magnesium salts, all of which comprise the hardness in water.



What the EPA Says About the Kinds of Contaminants That Might Be Found in Drinking Water

As water travels over the surface of the land or through the ground, it dissolves naturally occurring minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity. In order to ensure that tap water is safe to drink, the United States Environmental Protection Agency (EPA) and the California Department of Public Health (CDPH) prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. The federal Food and Drug Administration (FDA) and CDPH regulations

also establish limits for contaminants in bottled water, which must provide the same protection for public health.

Contaminants that may be present in source water include:

- Microbial contaminants, such as viruses and bacteria that may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife.
- Inorganic contaminants, such as salts and metals, that can be naturally occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining, or farming.

- Pesticides and herbicides, which may come from a variety of sources such as agriculture, urban storm water runoff, and residential uses.
- Organic chemical contaminants including synthetic and volatile organic chemicals that are by-products of industrial processes and petroleum production, and can also come from gas stations, urban storm water runoff, and septic systems.
- Radioactive contaminants that can be naturally occurring or be the result of oil
 and gas productions and mining activities.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. The tables in this report indicate which minerals and substances have been detected in the water provided by PWC. More information about contaminants and potential health effects can be obtained by calling the EPA Safe Drinking Water Hotline at 1-800-426-4791. You can also go to the following websites for more information:

EPA – www.epa.gov/safewater

CDPH - www.cdph.ca.gov/certlic/drinkingwater/Pages/default.aspx

What Are Drinking Water Standards?

Drinking water standards are regulations that the EPA sets to control the level of contaminants in the nation's drinking water. The EPA, the CDPH and the California Public Utilities Commission (CPUC) are the agencies responsible for establishing drinking water quality standards in California. These standards are part of the Safe Drinking Water Act's "multiple barrier" approach to drinking water protection, which includes assessing and protecting drinking water sources; protecting wells and surface water; making sure water is treated by qualified operators; ensuring the integrity of distribution systems; and making information available to the public on the quality of their drinking water. With the involvement of the EPA, the CDPH, the CPUC, drinking water utilities, communities and citizens, these multiple barriers ensure that tap water is safe to drink. The water delivered to your home meets standards required by the EPA, the CDPH and the CPUC. To recover the growing cost of meeting and maintaining EPA, CDPH and CPUC standards, Park submits a General Rate Case to the CPUC every three years. The CPUC is responsible for establishing water rates for Park.

If you would like more information about water quality, or to find out about upcoming opportunities to participate in public meetings, please call Bert Mason at 562-299-5117.

This report describes those contaminants that have been detected in the analysis of almost 200 different potential contaminants, nearly 100 of which are regulated by the EPA and the CDPH. Park is proud to tell you that there have been no contaminants detected that exceed any federal or state drinking water standards. Hundreds of samples every month and thousands every year by Park and MWD laboratories assure that all primary (health related) and secondary (aesthetic) drinking water standards are being met. See the tables on the following page to see how your water quality rates.

This report is intended to provide information for all water users. If received by an absentee landlord, a business, or a school, please share the information with tenants, employees or students. We will be happy to make additional copies of this report available. Complete records of water quality analyses are open for inspection by the public upon request. You may also access this report on the Park web page at www.parkwater.com.

Source Water Assessment Completed and Available

The 1996 Safe Drinking Water Act amendments required states to perform an assessment of potentially contaminating activities near drinking water sources of all water utilities. In California, the CDPH designated this to the utilities themselves. Park completed the Source Water Assessment in April of 2003. Park's wells are considered most vulnerable to the following activities associated with contaminants detected in the water supply: landfills and dumps, irrigated crops, and sewer collection systems. In addition, Park's well sources are considered most vulnerable to these additional activities: gas stations, dry cleaners, metal plating/finishing/fabricating shops, military installations, chemical/petroleum processing and storage facilities, and leaking underground storage tanks.

A copy of the complete assessment is available at Park Water Company and at the CDPH Glendale office. You may request a summary of the assessment by contacting Jeanne-Marie Bruno of Park Water Company at 562-299-5123 or by calling Mr. Kun Cheng, CDPH district engineer at 818-551-2019.

MWD completed its assessment in December of 2002. Its sources, including the Colorado River and the Sacramento-San Joaquin Delta, are considered most vulnerable to treated wastewater and recreation. Recreation may contribute sources of methyl tert-butyl ether (MTBE) and other fueling compounds, sediment, viruses, pathogens, and bacteria. Treated wastewater may contribute sources of nutrients, metals, and pathogens. A copy of the assessment is available to the general public upon request by calling CDPH at the above listed phone number.

Lead and Copper Although Park has not found lead or copper to be an issue in our water systems, the following information is required by the CDPH. If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. Park is responsible for providing high-quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at www.epa.gov/safewater/lead.

Fluoridation In 2013, Park started the operation of a new water well in this water system. Park installed fluoridation equipment to match the level of fluoride customers have received in the past from water we purchased from MWD for delivery to you.

Disinfection MWD uses monochloramine to disinfect the water they provide to Park. Park's new well also utilizes monochloramine to match MWD levels. Monochloramine is a combination of chlorine with ammonia for a longer lasting disinfectant that produces less disinfection by-products and less taste and odor. They have been used by water utilities throughout the nation for approximately 100 years.

Sensitive Populations May Be More Vulnerable

Some people may be more vulnerable to contaminants in drinking water than the general population. Persons with compromised immune systems such as those with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care provider. The EPA and the national Centers for Disease Control (CDC) have guidelines on appropriate means to lessen the risk of infection by *Cryptosporidium* and other microbial contaminants. These are available by calling the Safe Drinking Water Hotline at 1-800-426-4791.

WATER RESULTS Park Water Company – Compton/Willowbrook System 2013/2014 Annual Water Quality Report

Water Quality Parameters Detected in Park Water Company Sources (MWD and Wells)

PRIMARY STANDARDS - Mandatory (health-related)	State MCL	PHG or (MCLG)	Units of Measurement	MWD Range (including highest value)	Average for MWD	PWC Range (including highest value)	Average for PWC Wells (a)	PWC Date of Last Measurement (b)	Potential Sources of Contamination
INORGANIC CHEMICALS									
Aluminum	1,000	0.6	ppb	100 - 230	160	<50	ND	2011/12/13	Erosion of natural deposits; residue from some surface water treatment processes
Arsenic	10	0.004	ppb	2	2	<1 - 2.8	ND	2011/12/13	Erosion of natural deposits; runoff from orchards; glass and electronics production wastes
Barium	1	2	ppm	ND	ND	<0.1 - 0.12	ND	2011/12/13	Discharges of oil drilling wastes and from metal refineries; erosion of natural deposits
Combined Filter Effluent Turbidity (c)	0.3 at least 95% of the time	none	NTU	highest = 0.06	100%	NA	NA	continuous	Soil runoff
Fluoride (naturally occurring)	2	1	ppm	0.2 - 0.3	0.23	0.35 - 0.37	0.37	2011/12/13	Erosion of natural deposits; discharge from fertilizer and aluminum factories
Fluoride (treatment added) (d)	0.7 - 1.3 range*	1	ppm	0.7 - 1.0	0.8	NA	NA	2013	Water additive that promotes strong teeth
ORGANIC CHEMICALS									
Haloacetic Acids (HAA5)	60	none	ppb	11 - 19	16	NA	NA	2013	By-product of drinking water disinfection
Total Trihalomethanes (TTHMs)	80	none	ppb	40 - 50	45	ND	ND	2013	By-product of drinking water disinfection
RADIONUCLIDES									
Gross Alpha	15	(0)	pCi/L	<3 - 3	3	<3 - 6.26	ND	2013	Erosion of natural deposits
Gross Beta	50	(0)	pCi/L	<4 - 4	ND	NA	NA	2013	Decay of natural and man-made deposits
Uranium	20	0.43	pCi/L	2	2	<1 - 6.8	ND	2013	Erosion of natural deposits
LEAD AND COPPER RULE MONITORING	Federal Action Level	PHG	Units of Measurement	Number of Samples Taken	# of Samples Exceeding AL	PWC Range (including highest value)	Amount Detected at 90th Percentile**	PWC Date of Last Measurement (b)	Potential Sources of Contamination
Copper**	1,300	300	ppb	31	0	<50 - 320	100	2013	Internal corrosion of household plumbing
Lead**	15	0.2	ppb	31	0	<3 - 6.5	ND	2013	Internal corrosion of household plumbing

Water Quality Parameters Measured in the Distribution System

DISTRIBUTION SYSTEM	State MCL	PHG or (MCLG)	Units of Measurement	MWD Range (including highest value)	Average for MWD	PWC Range (including highest value)	Average for PWC	PWC Date of Last Measurement (b)	Potential Sources of Contamination
Chlorine residual (e)	MRDL = 4	MRDLG = 4	ppm	<0.2 - 2.9	2.3	0.34 - 3.0	1.89	weekly	Added for disinfection purposes
Chlorate	NL = 800	none	ppb	28 - 72	55	NA	NA	quarterly	By-product of drinking water disinfection
Color	15#	none	units	NA	NA	<1 - 12	<1	monthly	Naturally occurring organic materials
Coliform Bacteria	5% positive	(0)	% positive	0 - 0.2%	ND	0.0%	ND	weekly	Naturally present in the environment
Fluoride (treatment added) (d)	0.7 - 1.3 range*	1	ppm	0.7 - 1.0	8.0	NA	NA	daily	Water additive for dental health
Heterotrophic Plate Count Bacteria (HPC)	NS	none	CFU/mI	π	Π	<1 - 120	2	weekly	Naturally present in the environment
Haloacetic Acids (HAA5) ##	60	none	ppb	<1 - 22	18	3 - 19	11	quarterly	By-product of drinking water disinfection
Total Trihalomethanes (TTHMs) ##	80	none	ppb	12 - 60	58	12 - 53	49	quarterly	By-product of drinking water disinfection
N-Nitrosodimethylamine (NDMA)	NS	3	ppt	<1 - 11	ND	NA	NA	quarterly	By-product of drinking water disinfection
Turbidity	5 #	none	NTU	NA	NA	<0.1 - 2.77	<0.1	monthly	Soil runoff

SECONDARY STANDARDS Aesthetic standards (non-health related) CHEMICAL PARAMETERS	State MCL	PHG or (MCLG)	Units of Measurement	MWD Range (including highest value)	Average for MWD	PWC Range (including highest value)	Average for PWC Wells (a)	PWC Date of Last Measurement (b)	Potential Sources of Contamination
Aluminum	200	600	ppb	100 - 230	160	<50	ND	2011/12/13	Erosion of natural deposits; residue from some surface water treatment processes
Chloride	500	none	ppm	84 - 87	86	23 - 81	26	2011/12/13	Runoff/leaching from natural deposits, seawater influence
Color	15	none	units	1	1	<1	ND	2011/12/13	Naturally-occurring organic materials
Iron	300	none	ppb	<50	ND	<50 - 160	ND	2011/12/13	Leaching from natural deposits; industrial wastes
Manganese ###	50	none	ppb	<20	ND	<20 - 58	45	2011/12/13	Leaching from natural deposits
Odor threshold	3	none	units	3	3	1	1	2011/12/13	Naturally-occurring organic materials
Specific Conductance	1600	none	micromho/cm	870 - 900	890	560 - 870	575	2011/12/13	Substances that form ions when in water; seawater influence
Sulfate	500	none	ppm	180 - 200	190	70 - 150	74	2011/12/13	Runoff/leaching from natural deposits; industrial wastes
Total Dissolved Solids (TDS)	1,000	none	ppm	520 - 560	540	320 - 540	331	2011/12/13	Runoff/leaching from natural deposits
Turbidity	5.00	none	NTU	<0.1	ND	<0.1 - 0.73	0.02	2011/12/13	Soil runoff
ADDITIONAL PARAMETERS - Unregulated		D	ETECTED UNREGULA	ATED CHEMICALS THA	T MAY BE OF IN	ITEREST TO CONSUMER	s		
Aggressiveness Index (f)	NS	none	units	12.3	12.3	12.2 - 12.4	12.3	2011/12/13	
Alkalinity (as Ca CO3)	NS	none	ppm	76 - 130	110	180 - 200	190	2011/12/13	
Boron	NS	none	ppb	140	140	<100	ND	2011/12/13	
Calcium	NS	none	ppm	59 - 61	60	58 - 99	60	2011/12/13	
Chlorate	NL = 800	none	ppb	56	56	NA	NA	2013	
Corrosivity (Langelier Index) (g)	NS	none	positive/ negative	(+0.43) - (+0.53)	+0.53	(+0.84) - (+1.02)	+0.97	2011/12/13	
Hardness (Ca CO3)	NS	none	ppm	240 - 250	250	190 - 340	197	2011/12/13	
Hardness (grains)	NS	none	grains	14 - 14.6	14.6	11.1 - 19.9	12	2011/12/13	
Magnesium	NS	none	ppm	22	22	12 - 22	12	2011/12/13	
pH	NS	none	units	8.1	8.1	7.6 - 7.8	7.8	2011/12/13	
Potassium	NS	none	ppm	4 - 4.4	4	3 - 3.8	3.4	2011/12/13	
Sodium	NS	none	ppm	82 - 87	84	40 - 52	41	2011/12/13	
Total Organic Carbon (TOC)	Π	none	ppm	2 - 2.7	2.4	NA	NA	2011/12/13	

Key To Abbreviations and Footnotes

MCL = Maximum Contaminant Level, a drinking water standard

AL = Action Level

ND = Not detected

NL = Notification Level, the level at which notification of the public water system governing body is required (formerly called Action Level)

NS = No Standard

NA = Not Applicable at this time or not required to analyze for

CFU/ml = colony forming units per milliliter

NTU = Nephelometric Turbidity Units. This is a measure of the suspended material in water

TT = Treatment Technique

<= less than (essentially equivalent to ND)</pre>

ppm = parts per million or milligrams per liter

ppb = parts per billion or micrograms per liter

ppt = parts per trillion or nanograms per liter

pCi/L = picoCuries per liter

= a secondary (aesthetic) standard

= Average value equal to the highest quarter measurements in 2013

= new well 19C is being treated with polyphosphate to sequester high manganese while we conduct a one year study to determine the true value and whether a treatment plant is needed to remove high levels.

 $^{*}=\,$ Optimal treated fluoride levels for dental health is 0.8 mg/L with an operating control range from 0.7 to 1.3 mg/L.

** = Lead and Copper are regulated as a Treatment Technique under the Lead and Copper Rule. It requires water systems to take samples at "most vulnerable" consumer taps every three years and treatment steps must be taken if more than 10% of tap samples exceed the AL. (a) = The average is weighted according to the individual contribution in pumping by each well to the total (active wells only)

- (b) = The state allows us to monitor for some contaminants less than once per year because the concentrations of these contaminants in groundwater sources do not change frequently. Some of our data, though representative, are more than one year old. MWD water is monitored more frequently.
- (c) = The turbidity level of the MWD filtered water shall be less than or equal to 0.3 NTU in 95% of the measurements taken each month and shall not exceed 1.0 NTU at any time. Turbidity is a measure of the cloudiness of the water and is a good indicator of water quality and filtration performance.
- (d) = Fluoridation at MWD treatment plants started the last quarter of 2007
- (e) = Measured as Total Chlorine, the sum of the free chlorine and combined chlorine. MWD water is delivered with chloramine as the disinfectant.
- (f) = An aggressiveness index of 11 or greater indicates that the water is not aggressive (noncorrosive)
- (g) A positive number Langelier Index indicates that the water is noncorrosive

Definitions

Public Health Goal (PHG): The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the EPA.

Maximum Contaminant Level (MCL): The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste, and appearance of drinking water.

Maximum Contaminant Level Goal (MCLG): The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the EPA.

Maximum Residual Disinfectant Level (MRDL):

The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

Maximum Residual Disinfectant Level Goal (MRDLG):

The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Regulatory Action Level (AL): The concentration of a contaminant that, if exceeded, triggers treatment or other requirements that a water system must follow.

Primary Drinking Water Standard: MCLs and MRDLs for contaminants that affect health along with their monitoring and reporting requirements, and water treatment requirements.

Notification Level (NL): A health-based advisory level for an unregulated contaminant.

Treatment Technique (TT): A required process intended to reduce the level of a contaminant in drinking water.

Secondary Drinking Water Standard: Requirements that ensure the appearance, taste and smell of drinking water are acceptable.



P.O. Box 7002 9750 Washburn Road Downey, CA 90241-7002