

California Department of Public Health Product WorkSheet

Manufacturing Company Information
 General Electric
 Appliance Park AP2-120
 Louisville, Kentucky 40225
 Phone: 800-952-5039
 Website: www.geappliances.com

Product Brand: GE FXUVC
 Product Model: GE FXUVC
 CDPH registration # 13-2162
 Replacement Cartridge FXUVC

Operating Parameters	SI Units	Metric Units
Service Flow Rate	0.5 gpm	1.9 lpm
System Capacity	500 gallons or 6 months	(1893 L) or 6 months
Pressure	30-100 psi	2.1 - 7.0 Kg/cm ²
Temperature	40-100°F	4.4-37.8°C

GE FXUVC Performance Data Sheet

Contaminant Reduction Claims	Challenge Concentration	Maximum Permissible Product Water Concentration	Reduction Requirements	Reduction Average
Asbestos	10 ⁷ to 10 ⁸ fibers per liter	3 µg/L	99%	> 99.0%
Cyst	Minimum 50,000/mL		≥ 99.95%	99.99%
Lead (pH 6.5)	0.15 mg/L ± 10%	0.010 mg/L		99.20%
Lead (pH 8.5)	0.15 mg/L ± 10%	0.010 mg/L		99.30%
Mercury (pH 6.5)	0.006 ± 10%	0.002 mg/L		96.60%
Mercury (pH 8.5)	0.006 ± 10%	0.002 mg/L		91.70%
MTBE	0.015 mg/L ± 20%	0.005 mg/L		96.84%
Turbidity	11 ± 1 NTU	0.5 NTU		98.50%
VOC	0.3 mg/L	0.015 mg/L		>99.8%

Note: The manufacturer is required to re-test the product every 5 years for material safety, structural integrity and all performance claims made. Any change to the product must be submitted to the certification agency for a technical review. Testing may be required sooner based on the technical review.

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Note: The system must be installed and maintained according to manufacturer's recommendations, including replacement of filter cartridges. The contaminants or other substances removed or reduced by this system are not necessarily in your water. Please see Product Installation manual for details.